



HTX4150 4 Channel HT Amplifier

The HTX 4150 is an extremely flexible and powerful Home Theater or Multi-Channel power amplifier, which delivers up to 4 channels of high power, low distortion, and high-dynamic sound for your home theater or multi-channel needs.

The HTX 4150 can be configured as a 4/3 -or 2-channel amp. All adjacent channels can be bridged. For example, when configured as a 3-channel amp, the bridged center gets 400 watts each (8 Ohms), and the Left and Right get 150 watts (4 Ohms). Channels 1 and 2 can also be used as a subwoofer amplifier with x-over, phase and output level control.

Class D and fan-cooled, these amps are also perfect for use in racks, credenzas and cupboards, anywhere where cooling may be an issue.

SPECIFICATIONS

- OUTPUT POWER (RMS) @ 0.1% THD (Single Channel): 4 Ohms: 150W, 8 Ohms: 85W
- OUTPUT POWER (RMS) @ 1% THD (Single Channel): 4 Ohms: 200W, 8 Ohms: 120W
- ALL-CHANNEL OUTPUT POWER (RMS) @ 0.1% THD: 4 Ohms: 130W, 8 Ohms: 75W
- ALL-CHANNEL OUTPUT POWER (RMS) @ 1% THD: 4 Ohms: 175W, 8 Ohms: 100W
- Bridged Rating (RMS) @ 1% THD (Single Channel): 8 Ohms: 400W
- Frequency Response: 12-30kHz
- Signal to Noise Ratio (A-weighted): 105 dB
- Damping Factor (1kHz, 8 Ohms): 90
- Idle Current: 0.22 Amps
- Max Current @ All Channels Rated Power: 12.1 Amps
- Efficiency of Amplifier: 88%
- Amplifier Type: D
- Transformer Type: SMPS
- Fan-Cooled: Fan
- 12-Volt Triggers: Yes
- Auto-On Sensing: No
- Sub-Out: Yes
- Power Supply: 110/120 or 220/240V
- Rack Mountable: Yes
- Dimensions: (LxWxH): 15.16" x 16.81" x 3.46"
- Weight: 23 lbs
- Certification: CE/UL