



AMP300 High Current Amplifier

This 350-Watt A/B two-channel dual source amplifier is ideal for use as a remote amplifier to power your whole house audio system or as a single amp for a dedicated home theater or media room. The AMP 300 is 2 Ohm stable and includes two sets of speaker outputs with front panel controls. Auto-on signal sensing or 12-volt trigger, rear panel master level controls and dual line-level inputs with priority override switching. Dual voltage capable for 110V/220V.

SPECIFICATIONS

- Type: Class A/B
- Peak Power Output: 350 Watts per channel
- Maximum 8 ohm stereo output power: 150W
- Maximum 4 ohm stereo output power: 235W
- Maximum 8 ohm Bridged-Mono output power: 470W
- Frequency Response: (20Hz to 20kHz) +0.0dB, -0.5dB
- Impedance: 8 ohm to 2 ohm stable
- SNR: -103dB referred to rated power at 4 ohms
- Turn on options: manual on, signal sensing, and 12V Trigger mode
- Unique Automatic Dual Source Priority Switching with Speaker Level Input Option
- Automatic source switching
- High Output Toroidal Power Supply, High Capacitance and Ample Internal Heatsink
- Input and Output Terminals: Interrupting line input, main input/output, 12V trigger, speaker zone A output, speaker zone B output
- Rack Mountable
- Dual Source Switching
- Dimensions (Lx H x D): 16.5" x 5.25" x 14"
- Weight: 40 Lbs
- Warranty: 2 years